

EPOXY F 03567F

THIXOTROPIC UNIVERSAL ADHESIVE



03567F will be delivered in boxes to 6x 0,9kg (1 Box = 5,4kg). In the box there are also 12 pcs statics mixer



Product description

The Paste is a solvent-less thixotropic, blue plastic adhesive which consists of two Components on base of Epoxy and filler.

Application area

The paste can be used for:

Adhesion: Force-fit connection of precast concrete elements, concrete blocks, and -plates, concrete pipes, etc. Adhesion instead of plugging or screwing of concrete; stone, glass, metals together and among each other, as well as on horizontal, raked, vertical and overhead positions. The universal adhesive suits excellently on wet underground.

Anchorage: Dislocate and fixing of machine anchoring, door- and window frames, guard rails, step iron, tension rods, bolts, stone bolts, etc.

Repairs: Rigid, waterproof gouging of settlement- and shrinkage cracks, fill out holes cavity etc., as well as rigid sealing of areas that should be repaired, such as: Boxes, sewer, tanks.

Adhesion and Sealing for Hats, Shortliner and other materials in the sewer that can be bonded.

Characteristic from Epoxy F 03567F

- It shows an extremely high adhesive power and adherence
- It is thixotropic, so it is neither running nor effluent
- In the cured status it is still impact resistant and little elastic(93sH).

Ground

The contact areas have to be grease-, oil- and acid-free.

The underground can be dry or wet. Materials on cement: the sealcoating has to be removed. The cleaning can be mechanically or hydraulically.

Processing

Both components are mixed constantly and free of streaks with the molding press (Art.Nr: 31507) and the statics mixer (Art.Nr: 31929).

Pot life: 25 minutes
Processing temperature: +5°C till +25°C

Art.Nr.31507



Art.Nr.31929